



Engine
Rated Power
Blade Width
Maximum Speed
Draw Bar Pull
Operating Weight

Cummins 6LTAA9.3
162 kW @ 2,200 rpm
4,270 mm
40 km/h
89 kN
16,500 kg

4215D MOTOR GRADER

4215D SPECIFICATIONS >>>

ENGINE

Emission Regulation	Tier 2 / Stage II
Make	Cummins
Model	6LTAA9.3
Rated Power	162 kW @ 2,200 rpm
Maximum Torque	940 N.m @1400 rpm
Number of Cylinders	6
Aspiration	Turbo & air-to-air intercooled

TRANSMISSION

Transmission Type	Power shift
Torque Converter	Single stage, three elements
Maximum Travel Speed, fwd	40 km/h
Maximum Travel Speed, rev	26.2 km/h
Number of Speeds, fwd	6
Number of Speeds, rev	3

AXLES

Differential Type	Limited slip standard
Final Drive Type	Chain drive
Axle Oscillation	±16°
Front Axle, Wheel Lean Angle	Left / right 18°

STEERING

Steering Configuration	Load sensing steering
Steering Relief Pressure	16.7 MPa
Minimum Turning Radius	7,200 mm
Steering Angle	±50°
Frame Articulation Angle	±27°

BRAKES

Service Brake Type	Disc brake
Service Brake Location	Rear axle

TIRES

Tire Size	17.5-25
-----------	---------

HYDRAULIC SYSTEM

Main Pump Type	Gear
Main Relief Pressure	20 MPa
Main Pump Flow	122 L/min

WORKING CAPACITIES

Maximum Draw Pull	89 kN
Cutting Pressure	8,100 kg

TANDEM DRIVE PERFORMANCE

Height	648 mm
Width	226 mm
Center Distance	1,517 mm

MOLDBOARD PERFORMANCE

Bank Cut Angle	28~74°
Moldboard Lift Above Ground	600 mm
Moldboard Side Shift, left/right	660 / 740 mm
Maximum Sloping Angle	90°
Cutting Depth	680 mm
Circle Rotation	360°
Circle Diameter	1,455 mm
Circle Thickness	140 mm

DIMENSIONS

Wheelbase	6,230 mm
Overall Length	9,140 mm
Overall Width	2,675 mm
Overall Height with Cab	3,380 mm
Clearance under Front Axle	602 mm
Moldboard Standard Length	4,270 mm
Moldboard Standard Thickness	19 mm
Moldboard Standard Height	610 mm

OPERATING WEIGHTS


Operating Weight	16,500 kg
------------------	-----------

SERVICE CAPACITIES

Fuel Tank	348 L
Engine Oil	18 L
Cooling System	35 L
Hydraulic Reservoir	115 L
Transmission and Torque Converter	33 L
Tandems, each	90 L

OPTIONAL EQUIPMENT

Ripper
Front Dozer
Automatic Leveling System
Air Suspension Seat
Oil Bath Air Filter



Unit : mm

Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. Liugong standard and optional equipment may vary from region to region. Please consult your Liugong dealer for information specific to your area. Engine power kW is converted to horsepower (1 kW=1.3596 ps and 1 kW=1.3410 hp) in this file.

07/2025 Designed by LiuGong
Replace the previous versions of 03/2025