



VOLTO 45

*South African standard specification 2024

- tedder for 3-point hitch, cat. I+II
- working width 4.50 m
- drive 540 rpm
- 4 rotors each with 6 tine arms
- rotor diameter 1.50 m

CLAAS headstock suspension (CKL):

- damping elements for smooth trailing, even on bends
- direct support, entire weight is transferred to the lower links of the tractor
- automatic centring when lifting at the headland

PERMALINK drive concept:

- all rotors are pivoted individually for optimum ground following
- enables folding movements of up to 180° for retraction to a compact transport position

MAX SPREAD crop flow concept:

- tines arranged tangentially and inclined to the rear by 29.3°
- tines collect for 33% longer before they are in-line with the tractor's direction of travel
- for approx 10% higher work rates than with conventional tine arrangement
- even crop distribution

***South African standard specification 2024**

- 1) The above configuration is intended as general information.
- 2) The right to make modifications is reserved. Please always consult your CLAAS authorised importer as the sole source of current information on our vehicle's technical features.
- 3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.



- tool-free spreading angle adjustment
- dual tines Ø 9.5 mm each with 5 windings
- equal-length tines in Super C tine quality
- tine operating angle adjustable to $-7^{\circ}/0^{\circ}/+7^{\circ}$
- tine loss protection, integrated
- protective frame brackets made of glass fibre-reinforced polyamide
- rotor tyres 4x 16x6.50-8
- transport width 2.75 m
- weight: approx. 540 kg
- hydraulic requirements: 1x sa
- assembly time for basic machine approx. 5.5 hours

***South African standard specification 2024**

- 1) The above configuration is intended as general information.
- 2) The right to make modifications is reserved. Please always consult your CLAAS authorised importer as the sole source of current information on our vehicle's technical features.
- 3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.



Details of the selected product

Option	Description	Price
Additional Equipment		
VO_B02/0045	VOLTO 45	Standard
VO_D02/0010	Supported	Standard
VO_D04/0010	Three-point headstock	Standard
VO_E02/0100	Dual spring steel tines, diameter 9.5 mm	Standard
VO_R03/0550	+ Spare wheel with mount (16x6.5-8)	Standard
VO_S02/0020	Accessories, crate	Standard
VO_S03/0010	+ Warning signs	Standard
VO_S06/0030	Technical documentation, English	Standard
VO_T02/0020	Comes in crate	Standard

***South African standard specification 2024**

- 1) The above configuration is intended as general information.
- 2) The right to make modifications is reserved. Please always consult your CLAAS authorised importer as the sole source of current information on our vehicle's technical features.
- 3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.