

DEUTZ-FAHR 4090.4E Cab
*South African standard specifications 2024

Cab

- Cab with fixed front window
- Cab roof: 2 front + 2 rear work lights on cab roof
- Manual air conditioning
- Original sounproofed cab mounted on silent block, ventilation and heating system, opening rear windscreen with wiper, steering column with intergrated cluster holder, radio with loudspeakers, ambience light
- Left and right mirrors
- Rolling safety seat belt
- Seat(fabric)(mechanical suspension, adjustable weight and height)
- Tilting and telescopic steering column

*South African standard specifications 2024
1) The above configuration is intended as general information.
2) The right to make modifications is reserved. Please always consult your DEUTZ-FAHR authorised importer as the sole source of current information on our vehicles technical features.
3) All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

Machine equipment

Engine

SDF Stage 3 (Tier 3)4 cylinder engine with 4000cm capacity	Standard
Turbo intercooler	Standard
2200rpm Rated speed	Standard
Max. power (ECE R 120) 85hp/62.5kw	Standard
Electronic engine management	Standard
8" Air filter	Standard
Battery: 12V - 100AH - 850A(EN)/550A(IEC)/480A(DIN)	Standard

Transmission

Engine memory speed	Standard
Synchronized gearbox	Standard
Mechanical shuttle and splitter with lever on dashboard	Standard
Transmission 40km/h	Standard
5 Speed gearbox 30F + 15R with splitter and creeper	Standard

PTO

Mechanically operated PTO clutch	Standard
Fixed PTO shaft	Standard
Rear PTO: 540 - 540E and ground speed PTO	Standard

Axles + brakes

Mechanical front and rear differential lock and 4wd engagement	Standard
Without trailer brakes	Standard
Fully hydrostatic independent braking on a 4 wheels with oil immersed disc brakes	Standard
With seperate brake valve	Standard
Heavy duty rear axle	Standard

Steering

Hydrostatic steering with independent pump	Standard
Hydrostatic steering with double ram	Standard

*South African standard specifications 2024
1) The above configuration is intended as general information.
2) The right to make modifications is reserved. Please always consult your DEUTZ-FAHR authorised importer as the sole source of current information on our vehicles technical features.
3) All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

Hitch + lift + hydraulic system

Lifting capacity without additional assistor rams: 2500kg	Standard
Lift assistor rams (3500kg capacity)	Standard
3 Rear distributors with quick couplers (Spring + Detent + Float)	Standard
Mechanical rear lift controls on mudguards	Standard
3 Point linkage Cat 2 with fixed upper and lower links	Standard
Mechanical stabilizers	Standard
Mechanical rear lift with electrohydraulic "EASY LIFT" system	Standard
Open center hydraulic system with constant pump (42ltr/min)	Standard
Swinging drawbar Cat "A" + PTO protection	Standard

Tyres

320/70 R24 Front	Standard
420/85 R30 Rear	Standard
Tyre brand supplied by factory	Standard

Ballast

Ballast for rear wheels (2x2 Total 172kg)	Standard
Front cast iron weight frame (60kg) with hitch + 7 front weights (290kg). Total 350kg.	Standard

General

Fuel tank: 70ltr	Standard
Vertical exhaust pipe	Standard
Engine pre-heater kit	Standard
Toolbox	Standard
12V Electrical socket	Standard
Rotary beacon	Standard
Front headlights for right hand drive traffic	Standard

*South African standard specifications 2024
1) The above configuration is intended as general information.
2) The right to make modifications is reserved. Please always consult your DEUTZ-FAHR authorised importer as the sole source of current information on our vehicles technical features.
3) All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.