



Engine	Cummins QSL9.3
Rated Power	180 kW (241 hp / 245 ps) @ 2,200 rpm
Operating Weight	20,825 kg
Standard Bucket Size	4.0 m ³
Standard Breakout Force	178 kN
Standard Dump Clearance	3,303 mm

862H WHEEL LOADER

TOUGH WORLD. TOUGH EQUIPMENT.

862H SPECIFICATIONS >>>

ENGINE

Emission Regulation	Tier 3 / Stage III
Manufacturer	Cummins
Model	QSL9.3
Rated Power	180 kW (241 hp / 245 ps) @ 2,200 rpm
Peak Torque	1,187 N·m @ 1,300 rpm
Displacement	9.3 L
Number of Cylinder	6
Aspiration	Turbocharged & Air-to-air intercooled

TRANSMISSION

Transmission Type	Countershaft, power shift
Torque Converter	Single stage, three elements
Maximum Travel Speed, fwd	38 km/h
Maximum Travel Speed, rev	25.9 km/h
Number of Speed, fwd	4
Number of Speed, Rev	3

AXLES

Differential Front Type	Conventional
Differential Rear Type	Conventional
Axle Oscillation	±10°

STEERING


Steering Configuration	Flow Amplifying
Steering Relief Pressure	21 MPa

BRAKES

Service Brake Type	Wet discs brake
Service Brake Actuation	Hydraulic
Parking Brake Type	Drum
Parking Brake Actuation	Electro-hydraulic

HYDRAULIC SYSTEM

Main Pump Type	Gear
Main Relief Pressure	24 MPa
Raise	5.2 s
Dump Time	1.1 s
Float Down Time	3.0 s
Hydraulic Cycle Time	9.3 s



LOADER ARM PERFORMANCE WITH STANDARD BUCKET 4.0 m³

Tipping Load - Straight (ISO 14397-1:2007)	17,264 kg
Tipping Load - Full Turn (ISO 14397-1:2007)	14,742 kg
Max Bucket Breakout Force	178 kN
A Maximum Hinge Pin Height	4,530 mm
B Dump Clearance at Full Height Discharge	3,303 mm
C Dump Reach at Full Height Discharge	1,072 mm
D Maximum Digging Depth, Bucket Level	89 mm
S ₁ Rollback at Ground Level	44.3°
S ₂ Bucket Rollback at Carry	49°
S ₃ Bucket Rollback at Maximum Height	62.4°
S ₄ Maximum Dump Angle at Full Height	45°

BUCKET PERFORMANCE

Reference Bucket	3.0-6.0 m³
------------------	------------

DIMENSIONS

E Ground Clearance	460 mm
G Wheelbase	3,550 mm
H Cab Height	3,303 mm
J Wheel Tread	2,280 mm
K Width Over Tires	2,980 mm
L Length with Bucket Down	8,739 mm
M Turn Angle, Either Side	38°
P Rear Angle of Departure	29°
R ₁ Turning Radius, Bucket Carry	7,490 mm
R ₂ Turning Radius, Outside of Tire	6,650 mm
W Width Over Bucket	3,210 mm

TIRES


Tire Size	26.5-25-PR28/TT L-3
-----------	---------------------

OPERATING WEIGHTS

Operating Weight	20,825 kg
------------------	-----------

SERVICE CAPACITY

Fuel Tank	330 L
Engine Oil	28 L
Cooling System	35 L
Hydraulic System	273 L
Transmission and Torque Converter	35 L
Axles, Front/Rear	52 / 50 L



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. Liugong standard and optional equipment may vary from region to region. Please consult your Liugong dealer for information specific to your area. Engine power kW is converted to horsepower (1 kW=1.3596 ps and 1 kW=1.3410 hp) in this file.

03/2025 Designed by LiuGong
Replace the previous versions of 11/2024