



Mini Back-hoe Loaders (TLB's)

HD50M

Description

Introducing the Revaro HD50M mini TLB - a compact powerhouse designed to redefine versatility and efficiency in construction. Engineered with recession and innovation, the HD50M is your go-to solution for tackling a diverse range of tasks with ease.

Its robust build and advanced features ensure exceptional performance on various terrains. Whether it's excavation, loading, or landscaping, the Revaro HD50M Mini TLB stands ready to deliver reliability and productivity at every turn.



	Specs	HD50M
General	Engine power	50HP (37kW)
	Engine make	Yunnei YN25GB
	Drive	4WD
	Operating weight	2,800kg
	Tyre size	12-16.5
Loader	Dumping / load over / pin height	3,200mm
	Pin forward reach	1,000mm
	Dumping Height	2,100mm
	Max reach at full height (bucket dumped)	1,000mm
	Max digging depth	100mm
	Rollback at ground	45°
	Dump angle	45°
	Bucket/loader-arm breakout force	42kN
	Payload	1,000kg
	Loader bucket capacity	0.65m ³
Backhoe	Max digging depth	3,400mm
	Reach at ground to rear wheel/slew centers	4,670mm/4,620mm
	Reach at full height to slew center	1,900mm
	Side reach to center line	4,600mm
	Max working height / load-over height	5,000mm
	King post travel	No
	Boom Slew Angle	190°
	Bucket / dipper tearout force	52kN
	Excavator bucket capacity	0.05m ³
Dimensions	Overall length (transport / travel mode)	4,950mm
	Wheel base	1,780mm
	Rear wheel to slew center	550mm
	Min / slew ground clearance	240mm
	Height to top of cab / overall height	2,550mm
	Track width (rear / front)	1,410mm
	Width over bucket / width transport mode	1,680mm

