



中柳重工

ZHONGLIU HEAVY INDUSTRY



Laizhou Zhonghe Power Machinery Co., Ltd.

莱州中合动力机械有限公司有限公司
Laizhou Zhonghe Power Machinery Co., Ltd.



公司简介

COMPANY PROFILES

Laizhou Zhongliu Heavy Industry Machinery Co., Ltd. was established in 2006 and is located in the beautiful and rich industrial park of Shahe Town, Laizhou Bay, Jiaodong Peninsula. With a superior geographical location and 20 years of production and sales experience, the company's products include hydraulic machinery, loaders, internal combustion forklifts, off-road forklifts, excavators, concrete mixer trucks and other engineering machinery. The company is an engineering machinery enterprise that integrates research and development, manufacturing, production and sales. It is constantly committed to providing "one-stop" services for product technology research and development, from early scheme consultation, equipment installation and commissioning, to later operation and maintenance, and parts supply. Its core products have passed international certification, CE, ISO9001, and can provide customized design according to customer needs. The company has precision machining equipment and professional technical talents. Its product design is beautiful, reasonable, low energy consumption, high efficiency, and easy operation and maintenance, meeting the different needs of customers. The products are sold well throughout the country and at home and abroad, and are highly praised by users.

The company adheres to the principle of "survival through quality and development through reputation", continuously accelerates the development of new products, improves product performance to enhance the market competitiveness of the company's products, and upholds the concept of "integrity, innovation, eternity, and excellence". We are willing to sincerely cooperate with friends from all walks of life and discuss development plans together!





1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		ZL938 Detailed Parameters
卸货高度	Unloading Height mm	mm	4200
铲斗宽度	Bucket Width mm	mm	1900
发动机型号	Engine Model		490 Turbocharged Engine
发动机功率	Engine Power KW	kw	56
马力	Horsepower		76
驱动轴型号	Drive Axle Model		Lunbian Bridge
轮胎	Tyre		20.5-16
变速箱	Gearbox		Jinlite 265 Integral Gearbox
总重量kg	Overall Weight kg	kg	3500
额定输送能力kg	Rated Transfer Capacity kg	kg	1450
转弯半径	Turning Radius mm	mm	4650
卸载距离	Unloading Distance mm	mm	750
离地高度	Height From The Ground mm	mm	290
车轮节距	Wheel Pitch mm	mm	1520
轴距	Wheelbase mm	mm	2270
尺寸	Overall dimension mm	mm	6000/1860/2750



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		ZL940 Detailed Parameters
卸货高度	Unloading Height mm	mm	3500
铲斗宽度	Bucket Width mm	mm	2000
发动机型号	Engine Model		4102 Turbocharged Engine
发动机功率	Engine Power KW	kw	76kw
马力	Horsepower		108
驱动轴型号	Drive Axle Model		Lurbian Bridge
轮胎	Tyre		1670-20
变速箱	Gearbox		Jinlite Split Gearbox
总重量kg	Overall Weight kg	kg	4550
额定输送能力kg	Rated Transfer Capacity kg	kg	2000
转弯半径	Turning Radius mm	mm	4996
卸载距离	Unloading Distance mm	mm	800
离地高度	Height From The Ground mm	mm	360
车轮节距	Wheel Pitch mm	mm	1560
轴距	Wheelbase mm	mm	2330
尺寸	Overalldimensionmm	mm	6000/2000/2850



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		ZL948 Detailed parameters
卸货高度	Unloading Height mm	mm	3500
铲斗宽度	Bucket Width mm	mm	2000
发动机型号	Engine Model		4102 Turbocharged Engine
发动机功率	Engine Power KW	kw	76kw
马力	Horsepower		108
驱动轴型号	Drive Axle Model		Lurbian Bridge
轮胎	Tyre		1670-20
变速箱	Gearbox		Jinlite Split Gearbox
总重量kg	Overall Weight kg	kg	5200
额定输送能力kg	Rated Transfer Capacity kg	kg	1500
转弯半径	Turning Radius mm	mm	5200
卸载距离	Unloading Distance mm	mm	850
离地高度	Height From The Ground mm	mm	360
车轮节距	Wheel Pitch mm	mm	1560
轴距	Wheelbase mm	mm	2400
尺寸	Overall dimension mm	mm	6000/2000/2850



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		ZL958 Detailed parameters
卸货高度	Unloading height mm	mm	4500
铲斗宽度	Bucket width mm	mm	2000
发动机型号	Engine model		4102 turbocharged engine
发动机功率	engine power KW	kw	76kw
马力	horsepower		108
驱动轴型号	Drive axle model		Lunbian bridge
轮胎	tyre		1670-20
变速箱	gearbox		jinlite Split gearbox
总重量kg	Overall weight kg	kg	5600
额定输送能力kg	Rated transfer capacity kg	kg	1500
转弯半径	Turning radius mm	mm	5200
卸载距离	Unloading distance mm	mm	850
离地高度	Height from the ground mm	mm	360
车轮节距	Wheel pitch mm	mm	1560
轴距	Wheelbase mm	mm	2400
尺寸	Overall dimension mm	mm	7300/2000/2850



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		ZL968 Detailed parameters
卸货高度	Unloading height mm	mm	3500
铲斗宽度	Bucket width mm	mm	2200
发动机型号	Engine model		4108 turbocharged engine
发动机功率	engine power KW	kw	92kw
马力	horsepower		125
驱动轴型号	Drive axle model		Lunbian bridge
轮胎	tyre		1670-24
变速箱	gearbox		jinlite Split gearbox
总重量kg	Overall weight kg	kg	5800
额定输送能力kg	Rated transfer capacity kg	kg	2000
转弯半径	Turning radius mm	mm	5400
卸载距离	Unloading distance mm	mm	900
离地高度	Height from the ground mm	mm	370
车轮节距	Wheel pitch mm	mm	1600
轴距	Wheelbase mm	mm	2450
尺寸	Overall dimension mm	mm	6200/ 2200/ 2950



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		ZL998 Detailed parameters
卸货高度	Unloading height mm	mm	4500
铲斗宽度	Bucket width mm	mm	2200
发动机型号	Engine model		6105 turbocharged engine
发动机功率	engine power KW	kw	122kw
马力	horsepower		165
驱动轴型号	Drive axle model		Lunbian bridge
轮胎	tyre		17.5-25
变速箱	gearbox		315 Split gearbox
总重量kg	Overall weight kg	kg	7500
额定输送能力kg	Rated transfer capacity kg	kg	2500
转弯半径	Turning radius mm	mm	3800
卸载距离	Unloading distance mm	mm	1200
离地高度	Height from the ground mm	mm	370
车轮节距	Wheel pitch mm	mm	2200
轴距	Wheelbase mm	mm	2850
尺寸	Overall dimension mm	mm	7850/ 2400/3050



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		3T Detailed parameters
卸货高度mm	Unloading height mm	mm	3500
铲斗宽度mm	Bucket width mm	mm	2450
发动机型号	Engine model		Weichai 6 cylinder
发动机功率kw	engine power kw	kw	92
额定转速 (r/min)	Rated speed (r/min)		2000
马力	horsepower		125
驱动轴型号	Drive axle model		3 Ton Lunbian bridge
轮胎	tyre		17.5-25
变速箱	gearbox		428 gearbox
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	39
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	6110
总重量kg	Overall weight	kg	9850
额定载荷质量kg	Rated load mass kg	kg	3000
最大牵引力kn	Maximum traction kn	kn	101
最大上升力kn	Maximum rising force kn	kn	98
卸载距离mm	Unloading distance	mm	1010
车轮节距mm	Wheel pitch	mm	1850
轴距 毫米	Wheelbase	mm	2880
尺寸mm	Overall dimension	mm	7560*2520*3200



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		5T Detailed parameters
卸货高度mm	Unloading height mm	mm	3430
铲斗宽度mm	Bucket width mm	mm	3050
发动机型号	Engine model		Weichai 6 cylinder
发动机功率kw	engine power kw	kw	162
额定转速 (r/min)	Rated speed (r/min)		2200
马力	horsepower		220
驱动轴型号	Drive axle model		5 Ton Lunbian bridge
轮胎	tyre		23.5-25
变速箱	gearbox		ZL50 gearbox
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	42
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	7390
总重量kg	Overall weight	kg	17100
额定载荷质量kg	Rated load mass kg	kg	5000
最大牵引力kn	Maximum traction kn	kn	160
最大上升力kn	Maximum rising force kn	kn	160
卸载距离mm	Unloading distance	mm	1090
车轮节距mm	Wheel pitch	mm	2250
轴距 毫米	Wheelbase	mm	3200
尺寸mm	Overall dimension	mm	8250*2980*3420



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		6T Detailed parameters
卸货高度mm	Unloading height mm	mm	3450mm
铲斗宽度mm	Bucket width mm	mm	3050mm
发动机型号	Engine model		Weichai 6 cylinder
发动机功率kw	engine power kw	kw	178
额定转速 (r/min)	Rated speed (r/min)		2200
马力	horsepower		242
驱动轴型号	Drive axle model		6 Ton Lunbian bridge
轮胎	tyre		23.5-25
变速箱	gearbox		ZL60 gearbox
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	42
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	7290mm
总重量kg	Overall weight	kg	18000kg
额定载荷质量kg	Rated load mass kg	kg	6000kg
最大牵引力kn	Maximum traction kn	kn	170kn
最大上升力kn	Maximum rising force kn	kn	175kn
卸载距离mm	Unloading distance	mm	1220mm
车轮节距mm	Wheel pitch	mm	2180mm
轴距 毫米	Wheelbase	mm	3380mm
尺寸mm	Overall dimension	mm	8990*2980*3420



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		928 Mine Loader
卸货高度mm	Unloading height mm	mm	1800
铲斗宽度mm	Bucket width mm	mm	0.8m ³
发动机型号	Engine model		Dongfanghong 498 supercharging
发动机功率kw	engine power kw	kw	85
额定转速 (r/min)	Rated speed (r/min)		2200
马力	horsepower		115
驱动轴型号	Drive axle model		25J Weighted bridge
轮胎	tyre		9.75-18 1670-20
变速箱	gearbox		jinlite280
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	25
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	4600
总重量kg	Overall weight	kg	5300
额定载荷质量kg	Rated load mass kg	kg	2000
最大牵引力kn	Maximum traction kn	kn	45
最大上升力kn	Maximum rising force kn	kn	48
卸载距离mm	Unloading distance	mm	950
车轮节距mm	Wheel pitch	mm	1500
轴距 毫米	Wheelbase	mm	2450
尺寸mm	Overall dimension	mm	5600*1700*1900*1750



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		929 Mine Loader
卸货高度mm	Unloading height mm	mm	1750
铲斗宽度mm	Bucket width mm	mm	0.8m ³
发动机型号	Engine model		Dongfanhong 4105 Supercharging
发动机功率kw	engine power kw	kw	70
额定转速 (r/min)	Rated speed (r/min)		2200
马力	horsepower		95
驱动轴型号	Drive axle model		Twenty Weighted Bridge
轮胎	tyre		9.75-18 1670-20
变速箱	gearbox		Lean 280 Gearbox
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	25
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	4600
总重量kg	Overall weight	kg	5300
额定载荷质量kg	Rated load mass kg	kg	2000
最大牵引力kn	Maximum traction kn	kn	45
最大上升力kn	Maximum rising force kn	kn	48
卸载距离mm	Unloading distance	mm	950
车轮节距mm	Wheel pitch	mm	1500
轴距 毫米	Wheelbase	mm	2450
尺寸mm	Overall dimension	mm	5600*1700*1900*1750



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		936 Mine Loader
卸货高度mm	Unloading height mm	mm	2700
铲斗宽度mm	Bucket width mm	mm	0.8m ³
发动机型号	Engine model		Dongfanghong 6105 Supercharging
发动机功率kw	engine power kw	kw	103
额定转速 (r/min)	Rated speed (r/min)		2200
马力	horsepower		140
驱动轴型号	Drive axle model		Thirty Weighted Bridge
轮胎	tyre		1200-24 17.5-25
变速箱	gearbox		428 Gearbox
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	35
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	3200mm inside and 6200mm outside
总重量kg	Overall weight	kg	10800
额定载荷质量kg	Rated load mass kg	kg	3000
最大牵引力kn	Maximum traction kn	kn	75
最大上升力kn	Maximum rising force kn	kn	90
卸载距离mm	Unloading distance	mm	1350
车轮节距mm	Wheel pitch	mm	1800
轴距 毫米	Wheelbase	mm	2700
尺寸mm	Overall dimension	mm	6800*2000*2400*2600



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		Carry-Scraper
卸货高度mm	Unloading height mm	mm	1300
铲斗宽度mm	Bucket width mm	mm	1.0m ³
发动机型号	Engine model		Dongfanhong 4105 supercharging
发动机功率kw	engine power kw	kw	70
额定转速 (r/min)	Rated speed (r/min)		2200
马力	horsepower		95
驱动轴型号	Drive axle model		thirty Wet bridge
轮胎	tyre		1000-20 Underground Smooth Stab-proof Semi-solid Tire
变速箱	gearbox		fluid drive
最高速度 (km/h)	Maximum speed (km/h)	(km/h)	10
铲斗外转弯半径 (mm)	Outside turning radius of bucket	mm	2150mm inside and 4260mm outside
总重量kg	Overall weight	kg	7150
额定载荷质量kg	Rated load mass kg	kg	2000
最大牵引力kn	Maximum traction kn	kn	54
最大上升力kn	Maximum rising force kn	kn	48
卸载距离mm	Unloading distance	mm	860
车轮节距mm	Wheel pitch	mm	1020
轴距 毫米	Wheelbase	mm	2150
尺寸mm	Overall dimension	mm	6000*1300*2000



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		Pricking Table
发动机型号	Engine Model		Dongfanghong 4105 supercharging
发动机功率	Engine Power	kw	70
额定速度	Rated Speed	(r/min)	2200
马力	Horsepower		95
驱动轴型号	Drive axle Model		Thirty Wet Bridge
轮胎	Tyre		1000-20 Underground Smooth Stab-proof Semi-solid Tire
变速箱	Gearbox		Fluid Drive
最高速度 (km/h)	Maximum Speed (km/h)	(km/h)	10
铲斗外侧转弯半径 (mm)	Outside Turning Radius of Bucket (mm)	mm	Inner 2540mm Outer 4170mm
总重量kg	Overall Weight kg	kg	7400
车轮节距mm	Wheel Pitch mm	mm	1020
轴距 毫米	Wheelbase mm	mm	2200
尺寸mm	Overall Dimension mm	mm	6550*1300*2000



1. Simple and elegant appearance;
2. The new steering wheel adjustment mechanism improves operational comfort and adjustment reliability;
3. Vertical chimney can keep the engine away from dust, effectively enhance engine performance, and improve lifespan;
4. Increase and widen the cab to ensure that it does not obstruct the driver's field of view, making operation safer and more convenient;
5. LCD digital instrument panel, comfortable shock-absorbing seats, driver can drive for a long time without getting tired
6. Choose cast bridges for low maintenance costs in the later stage

Product Parameters

型号	Model		Pricking Table
发动机型号	Engine Model		Dongfanghong 4105 Boost
发动机功率	Engine Power	kw	70 kW
额定速度	Rated Speed	(r/min)	Two Thousand and Two Hundred
马力	Horsepower		Ninety-five
驱动轴型号	Drive axle Model		30 Wet Bridge
轮胎	Tyre		1000-20 downhole smooth anti puncture semi-solid tire
变速箱	Gearbox		Hydraulic drive
最高速度 (km/h)	Maximum Speed (km/h)	(km/h)	8.5
铲斗外侧转弯半径 (mm)	Outside Turning Radius of Bucket (mm)	mm	2150mm inside and 5000mm outside
总重量kg	Overall Weight kg	kg	7500kg
车轮节距mm	Wheel Pitch mm	mm	1020mm
轴距 毫米	Wheelbase mm	mm	2200mm
尺寸mm	Overall Dimension mm	mm	6550*1300*2530