



T6000 DELTA-PLUS SERIES

T6020 Delta-T6050 Delta-T6050 Plus-T6070 Plus



SPECIFICATIONS

Models	T6020 DELTA	T6050 DELTA	T6050 PLUS	T6070 PLUS
Engine				
Rated Power - ISO 14396/EC R120	kW/hp(CV) 82/112 93/127		93/127 104/141	
Rated Speed	rpm 2200			
Max. Torque ISO 14396	Nm@rpm 510@1250 555@1250		555@1250 625@1250	
Cylinders/displacement	cu.cm 4/4485 6/6728		6/6728	
Torque Rise	%(maximus) 43 38		38 39	
Aspiration	Turbocharged		Turbocharged	
Intercooling	air-to-air intercooled		air-to-air intercooled	
Electrical				
Standard alternator	Amps 120 Amp, 12 V		120 Amp, 12 V	
Battery capacity, CCA (standard/optional)	800/960		1300	
Transmission				
12x12 Synchro Command™	Standard		NA	
24x24 Dual Command™	Optional		Standard	
16x16 ElectroShift™	NA		Optional	
PTO - Standard "Soft Start"	Standard		Standard	
Axles				
Conventional 4WD Axle w/limitedslip	Standard		Standard	
Conventional 4WD Axle w/Terralock™	NA		Optional	
4WD track width adjustability	mm 1580 - 2337		1580 - 2337	
Wheelbase (4WD)	mm 2387 2627		2627	
Hydraulics				
Load-sensing hydraulic type	Open centre		Open centre (Closed centre with 16x16)	
Rear remotes	2 std, 3opt		2 std, 3 or 4 mech.	
Mid remotes	2 mech mid opt.		2 mech mid opt	
Main/implement pump flow	L/min 63		80 (113 with 16x16)	
Steering and services pump flow	L/min 40		40 (47 with 16x16)	
Total tractor hydraulic flow	L/min 103		120 (160 with 16x16)	
Draft control	Mechanical, EDC optional		EDC mechanical optional	
3-point hitch category	Cat II MDC, Cat II/IIIN EDC		Cat II MDC, Cat II/IIIN EDC Cat II/IIIN	
3-point hitch lift capacity - std./opt., kg at ball ends	4964 / 5997		5994 / 7864	

Models	T6020 DELTA	T6050 DELTA	T6050 PLUS	T6070 PLUS
Capacities				
Fuel tank	L 176	250	250	
Engine oil	L 10	15	15	
Hydraulic fluid	L 65	65 (62 16X16)		
Horizon™ cab w/hi-visibility panel				
Glass area including hi-visibility panel	m² 5.85		5.85	
Sound level	dBA 70-72	71-73	71-73	
Shipping weight				
Std. 4WD ROPS	Kg 4280	4700	NA	
Std. 4WD Cab	Kg 4750	4870	4870	
Height to top of ROPS	mm 2856	2898	NA	
Height to top of Cab	mm 2775	2819	2819	
Height to top of exhaust	mm 2726	2770	2770	



Visit our website: www.newholland.com/za



The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by CNHI INTERNATIONAL SA. Brand Marketing and Communication. creative-farm.it - 05/19 - RSA19101