



*Terms & Conditions Apply (5 YEAR/3000 HOURS)

6060 4WD



Engine Type	4-cylinder, 4-stroke, water-cooled, direct injection diesel
Max Engine Power	60 hp (45 kw)
Rated Engine Speed (rpm)	2100
Cylinders	4
Displacement	3533 cc
Fuel Tank Capacity	60 L
Transmission Type	Synchro Speed Gears with forward-reverse Synchro Shuttle
Number of Gears	15 F + 15 R
Tractor min and max speed	1,63 km/h - 31,69 km/h
Steering Type	Hydrostatic power
Steering Pump Output	17,5 l/min
PTO Type	Rear single lever independent
Max PTO Power	49 hp
PTO Speeds (rpm)	540 / 540E
ROPS	Standard
Cab with A/C	N/A
Total Weight (kg)	3336 kg
Front Axle / 4WD	Mechanical engagement, limited slip differential

Clutch Type	Dry dual, mechanically controlled / 12 inch
Max Lift Capacity (Lower Link)	2200 kg
Hydraulic Pump Output	57,5 lpm
Steering Pump Output	17,5 lpm
Three-Point Linkage	Cat II, fixed lower link
Auxiliary Remote Valves	2-spool standard
Hydraulic System	Full-live with position & draft control, dual spool auxiliary
Overall Length (mm)	4052 mm
Overall Width (mm)	1960 mm
Overall Height (mm)	2670 mm
Ground Clearance (mm)	350 mm
Wheelbase (mm)	2220 mm
Standard Tyres (Front)	9.5 x 24
Standard Tyres (Rear)	16.9 x 28
Turning Radius with Brakes (mm)	3800 mm
Turning Radius without Brakes (mm)	4200 mm
Brake Type	Oil immersed brakes (OIB) brakes foot operated, independently with provision of interlock, Hand brake

